

**Connect.
Command.
Control.**



ECMsa

Single-Axis All-In-One Motion Controller With Integrated Drive

Product Highlights

- > Compact Industrial Package for Streamlined OEM Integration
- > Rich Host Programming and Simulation Tools for Faster Software Development
- > Universal Motor Support for Maximum Motor/Stage Flexibility
- > Simple Configuration and Tuning with SPiiPlus MMI Application Studio
- > Max Drive Current: 10/20A at 150VDC, 15/30A at 100VDC
- > Drive Supply Input: 12-150VDC
- > Analog I/O: 1/1
- > Feedback Channels: 2 (AqB, SinCos, or Absolute)

> Digital I/O: 4/3

- Any can be used for general purpose
- 1 High-Speed Position Capture (MARK) Input
- 1 High-Speed Position Event Generation (PEG) Output
- 2 Limit Sensor Inputs
- 1 Brake Output
- 1 General Purpose Output
- 1 General Purpose Digital Input

> Functional Safety: STO, SS1

The **ECMsa** is a member of the Economical Control Modules (ECM) series of compact, highly integrated all-in-one motion controller and drives solutions designed to meet the needs of OEMs with cost-sensitive motion control applications. Its unique multiprocessor architecture leverages powerful control algorithms to achieve best-in-class performance, while its universal servo drive technology enables the system designer to easily control most types of motors and stages.



VALUE

Achieve excellent performance
at an economical price



FLEXIBILITY

Control various motion
stage technologies



INTEGRATION

Minimize design effort
with all-in-one industrially
packaged solution

For the latest version of this document visit our website at www.acsmotioncontrol.com

Smarter Motion

ACS
MOTION CONTROL

Specifications

Logic Supply Input

- Voltage range: 24 VDC $\pm 5\%$
- Maximum Input Current: 2A @ 22.8VDC
- Protections: Reverse Polarity

Drive Supply Input

- Voltage Range: 24-150VDC
- Maximum Input Current: Load Dependent
- Regeneration Resistor: not included

Amplifiers

- Number of Axes: 1
- Type: PWM 3-phase power bridge
- Motor Support
 - DC brush
 - 2 and 3 phase DC Brushless
 - 2 and 3 phase stepper: Open or closed loop, up to 1024 microsteps per step, dynamic current adjustment
- Output current: 5/10A, 10/20A, 15/30A at 100VDC only (continuous/peak, sine amplitude)
- Peak Current Time: 1 second
- PWM Switching Frequency: 20 kHz
- Minimum Load Inductance: 12.5 μ H per phase at 24Vdc bus (contact ACS to discuss applications with lower phase inductance motors)
- Max Output Voltage: 94% of Drive Supply input voltage
- Max Output Power:
 - 633/1258W (continuous/Peak) for 5/10A
 - 1266/2517W (continuous/Peak) for 10/20A
 - 1208/2393W (continuous/Peak) for 15/30A
- Protections: Short Circuit, Overcurrent, Overtemperature, Overvoltage, Undervoltage

Communication Interfaces

- SPI
 - Clock frequency up to 4 MHz
 - Can operate as Master or Slave
 - Up to 8 X SPI words per MPU Cycle
 - SPI word length is user configurable up to 16 bits
- Ethernet: 100 Mbps TCP/IP, Modbus, Ethernet/IP
- RS-232: Up to 115200 bps

Profile Generation

- 3rd order with smooth on-the-fly endpoint modification

Real-Time Programming

- Language: ACSPL+ object-oriented multi-threading
- Number of User-Programmable Buffers (Threads): 6
- Max Program Cycle Rate: 1 kHz
- Max Data Collection Rate: 20 kHz up to 4 variables
- RAM: 256MB
- Flash: 1GB

Servo Control Algorithms

- Standard
 - Cascaded PIVFF with loop shaping filters
 - Advanced feedforward
 - Dual loop
 - Disturbance rejection
 - Gain Scheduling
 - Field-oriented control
 - Space vector modulation
- Optional
 - Custom algorithms to meet demands of unique applications (contact ACS)
- Loop Sampling and Update Rate: 20 kHz position, 20 kHz velocity, 20 kHz current

Feedback

- Total Number of Channels: 2
- Incremental
 - AqB Encoders (Default type)
 - Max Frequency: 50 MHz
 - Electrical Interface: RS-422
 - Error Detection: Encoder not connected, illegal transition
 - SinCos Encoders (Optional)
 - Max Frequency: 500 kHz
 - Electrical Interface: 1 V peak to peak $\pm 10\%$
 - Max Multiplication: 65,536 (per full signal period)
 - Error Detection: Not connected
 - Compensation: Phase, Gain, Offset
 - Note: The drive automatically generates a digital quadrature echo of the SinCos encoder signal and sends it as an output to the AqB encoder pins
 - Digital Hall Sensor Inputs
 - Qty: 3
 - Electrical Interface: 5V, Single-ended, source, opto isolated
 - Note: Used for initial commutation, not for position servo feedback
 - Limit Sensor Inputs (Usable as general purpose)
 - Qty: 2
 - Electrical Interface: 5/24V $\pm 20\%$, opto-isolated, sink or source (jumper selectable)
- Absolute (Optional)
 - Types: BiSS-C, EnDat 2.1 & 2.2, Smart-Abs, SSI, Sanyo Denki, Panasonic A6
 - Max Frequency: EnDat- 8MHz, Smart-Abs-2.5MHz, Biss-C- 10MHz, Panasonic- 2.5MHz, Sanyo- 2.5MHz
 - Electrical Interface: RS-485
 - Error Detection: CRC, timeout, encoder not ready
- Supply Output: 5.1V. Total available current 1.5A for all analog encoders and 1.5A for all digital encoders
- ID Chip Interface: 1 per axis. For identification of compatible stages' configuration parameters.

Specifications Continued

Digital I/O (All are useable as general purpose)

- Total Quantity: 12/12
- High-Speed Position Capture (MARK) Input
 - Qty: 1
 - Electrical Interface: 5/24V $\pm 20\%$, Opto-isolated, two terminals
 - Max Capture Frequency: 1 per 2 MPU cycles
- General Purpose Input
 - Qty: 1
 - Electrical Interface: 5/24V $\pm 20\%$, Opto-isolated, two terminals
 - Max Capture Frequency: 2 kHz
- Limit Sensor Inputs
 - Qty: (See Feedback section for more details)
- High-Speed Position Event Generation (PEG) Output
 - Qty: 1
 - Electrical Interface: RS-422
 - Max Pulse Frequency: 10 MHz
 - Pulse Width Range: 40 ns to 671 ms
- Mechanical Brake Output
 - Qty: 1
 - Electrical Interface: 5/24V $\pm 20\%$, opto-isolated, sink or source (jumper selectable)
 - Output Current: 100 mA
- General Purpose Outputs
 - Qty: 1
 - Max Update Frequency: 1 kHz
 - Electrical Interface: 5/24V $\pm 20\%$, opto-isolated, sink or source (jumper selectable)
 - Output Current: 100 mA
 - Max Update Frequency: 1 kHz

Standards and Certifications

- CE
 - Self Declaration: Yes
 - Electrical Safety: IEC61800-5-1
 - EMC: IEC 61326-3-1, IEC 61800-3, IEC 61500-5-2
- UL
 - Electrical Safety: UL 61800-5-1
- TUV
 - STO & SS1 Functional Safety: IEC 61508, ISO13849, IEC 61800-5-2
- EtherCAT Technology Group Conformance

Analog I/O (All are useable as general purpose)

- Analog Inputs
 - Quantity: 1
 - Electrical Interface: $\pm 10V$ differential or 0-10V single ended
 - Resolution: 16 bit
 - Input Frequency: 5 kHz
- Analog Outputs
 - Quantity: 1
 - Electrical Interface: $\pm 10V$ differential
 - Resolution: 10 bit
 - Max Ripple: 25 mV
 - Max Load: 10 kOhm

Physical

- Dimensions: 128x139x55mm
- Weight: < 600g
- Environmental
 - Rated Operational Temperature: 0° to 50°C.
 - Humidity: 5 to 90% non-condensing humidity
 - Storage and Transportation Temperature Range: -25° to 60°C
 - Shock: 50 m/s² (5 G)
 - Vibration: 10 m/s² (1 G)

Optional Accessory Products

- XDMsa-ACC1: Mating Connector Kit
- STO-ACC1: STO Breakout Cable
- SPI-ACC1: SPI Breakout Cable
- RS232-ACC1: RS232 Adapter Cable

Functional Safety I/O (Optional)

- Safe Torque Off (STO) Input
 - Electrical Interface: Dual-channel 24V isolated
 - Safety Standards: See Standards and Certifications Section
- Safe Stop 1 (SS1) Feature
 - Deceleration time till STO activation: 40-460ms.
 - Exact deceleration time value is fixed (SS1-t functionality) and depends on product configuration (see Safety Manual for more details)

Ordering Options

Ordering Options	Field	Example User Selection	Values
Controller & Drive Axes	1	1	1
Current and Bus Voltage Rating	2	C	A = Reserved B = 5/10A up to 150VDC C = 10/20A up to 150VDC D = 15/30A up to 100VDC
500 kHz SinCos Encoder Channels ¹	3	1	0, 1, 2
Absolute Encoder Channels ¹	4	1	0, 1, 2
Functional Safety	5	T	N=None, T=STO & SS1
Autofocus	6	N	N = No A = Autofocus
Reserved	7	N	N
Reserved	8	N	N
Reserved	9	N	N
Reserved	10	N	N

Example: ECMsa-1C11T-NNNNN

Description: 10/20A, 1 channel 500kHz SinCos, 1 channel absolute encoder, STO & SS1

Field	1	2	3	4	5	6	7	8	9	10
PN	ECMsa	1	C	1	1	T	N	N	N	N

代理商：北京慧摩森电子系统技术有限公司
 地址：北京市朝阳区朝阳北路甲27号B1座302室
 电话：010-62311872
 传真：010-62316782
 邮箱：sales@bjsm.com.cn



微信公众号 抖音视频号
 携手慧摩森 创建灵巧之运动

For the latest version of this document visit our website at www.acsmotioncontrol.com

Smarter Motion

ACS
 MOTION CONTROL